# Eaton 3S UPS





#### Ideal for protecting:

- computers and peripherals
- Broadband modems (internet and TV)
- IP telephony equipment
- POS equipment

## Power protection for office and home computer equipment

#### **Protection against power problems**

- The Eaton 3S UPS helps to protect your computer equipment in case of everyday events such as lightning strikes, storms, over-demand on the utility grid, accidents, and natural disasters knocking out power without warning.
- In the event of a total blackout, the unit provides sufficient battery backup time to last through most power outages.
- The 3S also protects telephone, broadband and Ethernet line from "back door" power surges.
- The shutdown software makes it possible to automatically save your work and shut down your application without losing any data. Once the power is restored, you can continue working exactly where you left off.

#### Easy integration and installation

- Attractive design and glossy finish make the 3S a perfect fit for the modern office environment.
- The 3S comes with either 6 Schuko (DIN) or 6 French (FR) outlets for easy connection of typical computer configurations with peripherals (IEC model also available with 8 outlets).
- The 3S features a HID-compliant USB port (cable supplied), for automatic integration with common operating systems (Windows/Mac OS/Linux).
- Compact unit fits on or under your desk or can be mounted on a wall.
- Easy-to-replace battery helps to extend UPS service life.





### Eaton 3S UPS

- 1 3 Schuko or FR outlets with surge protection
- 2 3 Schuko or FR outlets with battery backup and surge protection
- 3 On / Off button + LED interface
- 4 USB port
- 5 Dataline protection
- 6 Replaceable battery
- 7 Reset button (circuit breaker)
- 8 Wall-mounting system



- 1 4 IEC outlets with surge protection
- 2 4 IEC outlets with battery backup and surge protection
- 3 On / Off button + LED interface
- 4 USB port
- 5 Dataline protection
- 6 Replaceable battery
- 7 Reset button (circuit breaker)
- 8 Wall-mounting system

TECHNICAL SPECIFICATIONS	Eaton 3S 550	Eaton 3S 700	
Rating (VA/W)	550 VA / 330 W	700 VA / 420 W	
Application			
Output connection (FR/DIN models)	3 outlets with battery backup and surge protection + 3 outlets with surge protection		
Output connection (IEC models)	4 outlets with battery backup and surge protection + 4 outlets with surge protection		
Characteristics			
Input voltage	Up to 161-284 V (adjustable)		
Output voltage	230 V (settable to 220 V, 230 V or 240 V)		
Frequency	50-60 Hz autoselect		
Input protection	Resettable circuit breaker		
Battery			
Battery type	Compact, sealed lead-acid (replaceable)		
Battery test	Yes	Yes	
Cold start (no mains power)	Yes	Yes	
Deep-discharge protection	Yes	Yes	
Battery replacement indicators	LED	LED	
50% load backup	<u>10 min</u>	9 min	
70% load backup	6 min	6 min	
Communication			
Communications port	HID-compliant USB port for automatic integration with most common operating systems (Windows XP, Vista and 7, Linux, Mac OS X), cable supplied		
Line protection	Tel/fax/modem/internet/Ethernet		
Standards compliance			
Safety	IEC/EN 62040-1, CE mark		
EMC	IEC 62040-2		
Dimensions, weight and colour			
Dimensions H x W x D	86 x 140 x 335 mm	86 x 170 x 335 mm	
Weight	2.9 kg	3.8 kg	
Colour	Black	Black	
Customer service & support			
2-year warranty	Standard product exchange, including battery		
Warranty+	Optional 3-year warranty (depending on the country please visit www.eaton.com/powerquality)		

Part numbers	550	700
French sockets (FR)	3S550FR	3S700FR
Schuko sockets (DIN)	3S550DIN	3S700DIN
IEC sockets	3S550IEC	3S700IEC

