


The **Batium** range controlled by **microprocessor** guarantees you the maximum effectiveness and security.



15 ▶ 130 Ah
GEL/AGM/VRLA/LIQUIDE



Ref. **024496**



The charge is **automatic/without supervision**.



50% shorter charge time compared to a traditional charger. Batium ensures an ultra-quick and safe charge, by providing a **constant average current** during "boost" phase.



Batium ensures a **100% charge** of all lead-acid batteries* (IwUoU curve). A standard "automatic" charger, W2 or WU curve, charges up to 90% only.



Batium is a microprocessor controlled **smart charger**, that constantly analyses the state of the battery and regulates the charge according to the battery's needs.




Deeply discharged batteries that are still in a good state of health (eg : Lights on when the vehicle is stopped) could have a voltage as low as 1V. Batium can **charge from 1 volt**, whereas most chargers cannot.











Protection of the on-board electronics. No need to disconnect the battery from the vehicle. No risk of sparks or short-circuits, and no current is supplied to the clamps unless they are connected to the battery terminals.

IwUoU



CE EN 60335-2-29

 50/60Hz				EFFICACE /RMS	MOYEN/AVERAGE						
					Reg 1	Reg 2	Reg 3				
230V	105W	6-12V	2	11A	3	7	-	15A	28x20x12 cm	4,2 kg	-