



Model		PRO600I	PRO1000I	PRO1500I
Capacitate		600VA/360W	1000VA/600W	1500W/900W
Alimentare	Tensiune	110/120 VAC sau 220/230/240VAC		
	Plaja tensiunii de alimentare	81~145 VAC/ 162~290 VAC		
	Frecventa	60/50 Hz		
Iesire	Tensiune (mod acumulator)	± 10%		
	Forma de unda (mod acumulator)	dreptunghiular		
	Frecventa (mod acumulator)	60 Hz sau 50 Hz± 1 Hz		
	Timp transfer	2-6 ms, 10 ms max.		
Protectii	Protectie totala	Protectie la supraincarcare		
Interfata de comunicare		USB		
Acumulatori	Tip	Acumulatori etans plumb acid fara intretinere		
	Reincarcare	Dupa descarcare totala se incarca 6-8 ore la 90% din capacitate		
	Autonomie (la sarcina maxima)	3 min		
	Configuratie	12V7Ahx1	12V7Ahx2	12V9Ahx2
Semnalizari	Pe acumulator	Semnal acustic la 10 sec.		
	Acumulator descarcat	Semnal acustic in fiecare sec.		
	Suprasarcina	Semnal acustic de doua ori pe sec.		
	Avertizare inlocuire acumuloare	Semnal acustic in fiecare 2 sec.		
	Eroare	Semnal acustic continuu		
Altele	Zgomot la 1m	< 40 dB		
	Temperatura de functionare	0 -40 °C (fara condens)		
	Umiditate	0 - 95%		
	Greutate neta (kg)	4.25	7.8	10.1
	Dimensiuni aparat (mm)	298x101x142	338x149.3x162	380x158x198