

Akin 3000

PN: PWAV-30002AK-AZ01B

EAN: 6422956006198

The worthy protector



Digital display



Time delay function



Selectable input voltage range



★ Features

- ⊕ Microprocessor control guarantees high reliability
- ⊕ Selectable input voltage range
- ⊕ Time delay function eliminates transients that can affect connected equipment
- ⊕ Under-voltage, over-voltage, over-heat and over-current
- ⊕ Provides stable output voltage
- ⊕ Provides surge and spike suppression

📄 Specifications

Capacity	3000VA / 2400W
Socket type	1 x Schuko, 1 x IEC C19
Input	
Nominal Voltage	220 VAC
Voltage Range	110 VAC - 270 VAC or 140 VAC - 260 VAC (Selectable)
Frequency Range	60 Hz or 50 Hz
Output	
Nominal Voltage	220 VAC
Voltage Regulation	± 10%
Efficiency	
Normal Mode	95%
AVR Mode	92%
Protection	
Delay Time	3 minutes or 10 Seconds

Full Protection	Over-voltage Under-voltage Over-heat Over-current
Indicators	
LED Indicator	Normal indicator AVR indicator Delay time setting Fault indicator
Normal Mode	Green lightning
Activate Voltage Range Switch Mode	Yellow & Green LED lightning
Output Adjustable Voltage Range Mode	Red & Green LED lighting
Time Delay	Red LED Flashing & Green lighting
Digital Display	Input and output voltage




Physical

Dimension, D X W X H (mm)	297.1 x 150 x 199
Net Weight (kgs)	8.56

Environment

Operating Temperature	0-40°C
Humidity	0-90 % relative humidity (Non-condensing)

Logistics

 Carton Box Size	295 x 250 x 350 mm
 Pieces in the Carton Box	1 pcs / ctn
 Net & Gross weight / CTN	8.56 kg / 10.2 kg

Certificates

